

I9000

ZERO CLEARANCE OPTION



Big, bold and striking, the I9000 adds great visual impact and plenty of heat for large, spacious areas.

- Efficiently heats areas up to 240m²
- Superior heat from a fully finned 6mm cast iron firebox and triple air combustion system
- Suitable for masonry recess installations and ZC applications
- Fitted with masonry bricks and steel baffle for durability
- Standard 2-speed convection fan for faster heat circulation

MODEL	MAW2052
FINISH	Metallic black paint with black trim Metallic black paint with titanium trim
FIREBOX	Cast Iron
LOUVRE/GRILL	Black
EST. PEAK OUTPUT	24kW
APPROX. HEAT AREA	240m ²
EMISSIONS	1.2g/kg
EFFICIENCY	55%
CIRCULATION	2-speed convection fan
DIMENSIONS (WxDxH)	760 x 565 x 695mm (Insert) 852 x 612 x 786mm (ZC)
FIREBOX DIMENSIONS (WxDxH)	590 x 434 x 341mm
LOG SIZE	540mm

Minimum distance to heat sensitive materials (mm) and floor protector sizes as per standard AS/NZS 2918:2001

NOTE: INSULATED FLOOR PROTECTORS

For detailed design and specifications of insulated floor protector required please refer to the installation manual.

MODEL	TYPE	D	H	W	F	FH	FW	FF	HW*	HD*
I9000	INSERT	565	695	760	217	741	1024	348	1025	525
I9000 ZC	INBUILT	612	786	852	264	847	1024	348	1025	525

